

ITB 18-0028, FIELD SERVICE VEHICLE
EXHIBIT A: FIELD SUPPORT TRAILER SPECIFICATIONS

TRAILER SPECIFICATIONS: Unless otherwise specified, the items listed in this Exhibit, Field Support Vehicle Specifications represent Citizens required specifications. In addition to the required specifications, Citizens has also included preferred customization specifications.

Trailer proposed MUST be in new, unused condition. Citizens will not accept a proposal for Trailer that has been previously used in any capacity.

The Trailer purchased and delivered MUST comply with all U.S. Federal Motor Vehicle Safety Standards, State of Florida regulations and requirements.

TABLE 1: Required Standard Specifications		
Qty	UOM	Description
1	EA	Wells Cargo - MotorTrac - Model# MTG85X4427
1	EA	MotorTrac Gooseneck
1	EA	Gooseneck
1	EA	Flat Front
1	EA	Flat Roof
1	EA	44ft Long
1	EA	8-1/2ft Wide
1	EA	Steel Frame
1	EA	2-5/16in 25,000lb Ball Coupler - Square.
1	EA	UPG-No Beavertail.
1	EA	Z Crossmembers
44	FT	Crossmembers 16in On Center
1	FT	4in x 8in Tube Main Rails.
1	PR	Heavy Duty Rear Cornerpost Jacks - 3,000lb Cap
1	PR	UPG-Double Leg Hydraulic Landing Gear (Req. Batt Opt)
1	EA	Hat Section Roof Bows
44	FT	Roof Bows 16in On Center
1	PR	5/16"Safety Chains w/ 5/16"Clevis Hook, Latch
44	FT	UPG-6in Extra Height.
44	FT	UPG-92-3/4in Hat Posts
44	FT	Vertical Posts 16in On Center
1	EA	8ft Upper Deck.
1	EA	56in Riser Height.
1	EA	Chassis Fully Undercoated with CPC
1	EA	0 Degree Angle
1	EA	Tandem Axle
1	EA	Wide Track
1	EA	Breakaway Kit
2	EA	Electric Drum Brakes (DOT Batt & Breakaway Req'd)
2	EA	8 Bolt Pattern

**ITB 18-0028, FIELD SERVICE VEHICLE
EXHIBIT A: FIELD SUPPORT TRAILER SPECIFICATIONS**

2	EA	Oil Bath Hubs for 6K-10K Axles
1	EA	5/8in Studs
1	EA	Rubber Ride Suspension
2	EA	8,000lb Axle
4	EA	LT215/75R17.5H Radial 8B Black Steel Wheel Notes: Make These Silver Wheels
1	EA	Spare LT215/75R17.5H Radial 8B Silver Conv. Wheel
1	EA	34in x34in Below Floor Tire Storage.
1	EA	8in x 29in Riser Crank handle Door.
1	EA	16in x 48in ATP Riser Wall Access Door.
1	EA	92.5" wide Rear Ramp Door - Standard MT
1	EA	UPG-Black Coin Rubber Rear Ramp Door Covering.
1	EA	Cargo Vice Lock
1	PR	Bogey Wheels.
1	EA	UPG-85 1/8"W Aluminum Ramp Extension
1	EA	3/4 PlexCore Ramp Decking.
1	EA	UPG-36 x 78 Side PT Door - RH Hinge - Recessed Step.
1	EA	40"W Aluminum Single Slide Out Step
1	EA	36 x 78 Side PT Door - LH Hinge - Recessed Step.
1	EA	40"W Aluminum Single Slide Out Step
2	EA	Install 12" x 21" Fixed Clear Window In Each Side Door
44	FT	White Vinyl Ceiling Liner
44	FT	3/4in PlexCore Decking.
44	FT	UPG-Black Marble Vinyl Floor Covering
5	FT	Recessed Horizontal Steel E-Track (Welded).
10	FT	Recessed Horizontal Steel E-Track (Welded).
4	FT	Recessed Horizontal Steel E-Track (Welded).
44	FT	Insulated Ceiling (requires ceiling liner)
1	EA	2inx3in Frame Partition Wall w/o Door.
7	FT	Insulated Sidewalls
1	EA	Wht Alu Straight Wb 72x30x40 / GV Top.
1	EA	72in Wide x 18.5in Tall White Alum OH Cabinet.
2	EA	96in Wide x 18.5in Tall White Alum OH Cabinet.
20	SF	Gray Laminate countertop
1	EA	24in (W) x 35in (H) x 30in (D) White Alum 4-Drawer Cabinet
30	SF	Gray Laminate countertop
1	EA	White Aluminum 24in x 24in Closet w/Rod.
12	EA	Locking Cabinets Latches IPO Std. Non-Locking
21	SF	Gray Laminate countertop
44	FT	9mm White Vinyl Sidewall Liner

**ITB 18-0028, FIELD SERVICE VEHICLE
EXHIBIT A: FIELD SUPPORT TRAILER SPECIFICATIONS**

44	FT	Insulated Sidewalls
4	EA	30in x 26in CS Horiz. Radius Slider Window.
36	FT	36in Charcoal Gray Track Pad Wall Guard.
4	EA	5,000lb Square D-Ring with Welded Plate
4	EA	12 Volt LED Dome Light (Requires 12v Wall Switch)
1	EA	12v Cargo Light.
1	EA	License Plate Bracket w/Logo and Internal Light
1	EA	LED Amber Clearance Front 3 Light Center Cluster.
9	EA	LED Clear Lens Red Clearance Lights
10	EA	LED Clear Lens Amber Clearance Lights
1	PR	LED Wraparound Tail Lights
1	EA	S.A.E. Color Coded 12 Volt Electrical System
1	EA	Seven Way Trailer End Connector
2	EA	12v Surface-Mount Switch
1	EA	Stainless Steel Cap
44	FT	Bonded Exterior Sidewalls No Riveted Seams.
44	FT	Polar White
44	FT	.040 Aluminum Exterior (White or Black Only)
1	PR	12v LED Side Surface Mount Back-Up Light.
44	FT	DOT Tape
1	EA	Chrome Rear Header (Must Inc. Chrome Rear Corners)
1	PR	Chrome Rear Corners (Must Inc. Chrome Rear Header)
1	PR	Stainless Steel Front Corners
44	FT	One Piece Aluminum Roof
1	EA	24"H ATP Stoneguard
3	EA	15Mbtu DOMETIC Roof Mount A/C
6	EA	120v 4ft Fixture w/ Diffuser and 2 LED Bulbs.
1	EA	120V 3-Way Interior Wall Switch
1	EA	120v 15a 1g Switch.
2	EA	120/240v 50a Power Cord/Plug - 25ft.
2	EA	120/240v 50a Electric Service Panel.
1	EA	120/240v 50a Motorbase Receipt w Lock Connect.
2	EA	50 AMP Transfer Switch
12	EA	120v 15a Duplex 1g Receipt (2 Outlet).
4	EA	120v 15a Duplex 1g Exterior GFI Receipt (2 Outlet).
2	EA	14in x 14in Non-Powered Roof Vent
1	PR	24" Scissor Jacks
1	EA	**10KW Onan Commercial Diesel Pkg (Riser Tank) Items in package follow:
1	EA	Fuel Gauge (included in package)
1	EA	100Amp Deep Cycle Battery & Charging System (included in package)

**ITB 18-0028, FIELD SERVICE VEHICLE
EXHIBIT A: FIELD SUPPORT TRAILER SPECIFICATIONS**

1	EA	10.0KW Onan Commercial Diesel Generator (included in package)
1	EA	Aluminum Cast Lockable Fuel Door (included in package)
1	EA	Compartment, Stationary Commercial diesel Generator 10KW (included in package)
1	EA	Access Door, Generator, 29 1/4"H x 49 1/4"W (included in package)
1	EA	Carbon Monoxide Detector - 9V (pkg) (included in package)
1	EA	25gal In-Riser Diesel Fuel System (included in package)
1	EA	Remote Start with Hour Meter(pkg) (included in package)

Table 2: Optional Pricing Specifications		
Qty	UOM	Description
2	EA	8ft x 8ft Galvanized Metal Platforms. Notes: These two platforms start immediately from the front portion of the trailer over the Gooseneck and have a cut out around the air conditioner to avoid interference. The platforms shall support the weight of various satellite and electronic equipment.
1	EA	Custom Aluminum Ladder: Notes: A custom aluminum ladder will attach to the front of the trailer and to the platform and wrap around the nose of the trailer. The tubes of the ladder will be 3" x 2" inch minimum in diameter to provide for a wire conduit to the satellite platform.